

## Multilayer Chip Power Inductors (CK series P type)

## CKP2012NR47M-T



## ■ Features

- Item Summary  
0.47uH±20%, 1.2A, 0805/2012 (EIA/JIS)
- Lifecycle Stage  
Mass Production
- Standard packaging quantity (minimum)  
Taping Embossed 3000pcs

## ■ Products characteristics table

|                               |                |
|-------------------------------|----------------|
| Inductance                    | 0.47 uH ± 20 % |
| Case Size (EIA/JIS)           | 0805/2012      |
| Rated Current (max)           | 1.2 A          |
| DC Resistance (max)           | 80 mΩ          |
| DC Resistance (typ)           | 60 mΩ          |
| LQ Measuring Frequency        | 1 MHz          |
| Operating Temp. Range         | -40 to +85 °C  |
| RoHS2 Compliance (10 subst.)  | Yes            |
| REACH Compliance (173 subst.) | Yes            |
| Halogen Free                  | Yes            |
| Soldering                     | Reflow/Wave    |

## ■ External Dimensions

|             |              |
|-------------|--------------|
| Dimension L | 2.0 ±0.2 mm  |
| Dimension W | 1.25 ±0.2 mm |
| Dimension T | Max 1.0 mm   |
| Dimension e | 0.5 ±0.3 mm  |

2017.05.03

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
 Before making final selection, please check product specification.